


Gewickeltes Rohr

GFK Rohre

Resin Type: Derakane 411 with 0.5 mm inner liner



#	DN (mm)	Pmax. (bar)	I.D. (mm)	Wall Thickness (mm)	O.D. (mm)	L (Length) (m)	Article Number
1	25	10	25	3.0	31	4.0	PMA-25-10/400
2	40	10	40	3.0	46	4.0	PMA-40-10/400
3	50	10	50	3.0	56	4.0	PMA-50-10/400
4	50	10	50	3.0	56	5.8	PMA-50-10/600
5	65	6	65	3.0	71	5.8	PMA-65-06/600
6	80	6	80	3.0	86	5.8	PMA-80-06/600
7	100	6	100	3.0	106	5.8	PMA-100-06/600
8	125	6	125	3.0	131	5.8	PMA-125-06/600
9	150	6	150	3.5	157	5.8	PMA-150-06/600
10	200	6	200	3.5	207	5.8	PMA-200-06/600
11	250	6	250	3.5	257	5.8	PMA-250-06/600
12	300	6	300	4.0	308	5.8	PMA-300-06/600

Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.