

Losflansche (Loser Flansche)

Typ BRP and BR / geeignet für GFK Bund (Typ TSS/TSC & SF Rotec)

Drilling Standard: JIS B2220 30K



| # | DN (mm) | Pmax (bar) | D (mm) | d1 (mm) | d10 (mm) | r1 (mm) | k (mm) | Holes (no.) | d2 (mm) | b1 (mm) | Resin Type | Product Color | Article Number |
|---|------------|---------------|-----------|------------|-------------|------------|-----------|----------------|------------|------------|------------|---------------|-------------------|
| 1 | 350 | 25 | 585 | 410 | 406 | 5 | 495 | 16 | 33 | 66 | Vinylester | Grey | BR-350-410-25/30K |
| 2 | 350 | 32 | 585 | 410 | 406 | 5 | 495 | 16 | 33 | 75 | Vinylester | Grey | BR-350-410-32/30K |
| 3 | 400 | 25 | 640 | 462 | 458 | 6 | 560 | 16 | 39 | 70 | Vinylester | Grey | BR-400-462-25/30K |
| 4 | 400 | 32 | 640 | 462 | 458 | 6 | 560 | 16 | 39 | 80 | Vinylester | Grey | BR-400-462-32/30K |

Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

28-05-2026