

Rotec Bridas ciegas

Resina Derakane 411 (o equivalente)

Drilling Standard: ANSI B16.5 Class 300



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
1	25	16	125	89	4	19	20	BFS-25-16/300
2	40	16	154	114	4	22	20	BFS-40-16/300
3	50	16	164	127	8	19	20	BFS-50-16/300
4	65	16	200	149	8	22	20	BFS-65-16/300
5	80	16	220	168	8	22	25	BFS-80-16/300
6	100	16	255	200	8	22	25	BFS-100-16/300
7	125	16	285	235	8	22	30	BFS-125-16/300
8	150	16	325	270	12	22	28	BFS-150-16/300
9	150	20	325	270	12	22	30	BFS-150-20/300
10	150	25	325	270	12	22	35	BFS-150-25/300
11	200	16	380	330	12	25	35	BFS-200-16/300
12	200	20	380	330	12	25	40	BFS-200-20/300
13	200	25	380	330	12	25	44	BFS-200-25/300
14	250	16	450	387	16	29	40	BFS-250-16/300
15	250	20	450	387	16	29	44	BFS-250-20/300
16	250	25	450	387	16	29	52	BFS-250-25/300

Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

08-02-2024

Rotec Bridas ciegas

Resina Derakane 411 (o equivalente)

Drilling Standard: ANSI B16.5 Class 300



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
17	300	16	540	451	16	32	48	BFS-300-16/300
18	300	20	540	451	16	32	52	BFS-300-20/300
19	300	25	540	451	16	32	60	BFS-300-25/300
20	350	16	585	514	20	32	52	BFS-350-16/300
21	350	20	585	514	20	32	60	BFS-350-20/300
22	350	25	585	514	20	32	68	BFS-350-25/300
23	400	16	660	572	20	35	60	BFS-400-16/300
24	400	20	660	572	20	35	68	BFS-400-20/300
25	400	25	660	572	20	35	74	BFS-400-25/300
26	450	16	710	629	24	35	68	BFS-450-16/300
27	450	20	710	629	24	35	74	BFS-450-20/300
28	450	25	710	629	24	35	85	BFS-450-25/300
29	500	16	775	686	24	35	74	BFS-500-16/300
30	500	20	775	686	24	35	80	BFS-500-20/300
31	500	25	775	686	24	35	90	BFS-500-25/300
32	600	16	915	813	24	41	85	BFS-600-16/300
33	600	20	915	813	24	41	95	BFS-600-20/300

Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

08-02-2024

Rotec Bridas ciegas

Resina Derakane 411 (o equivalente)

Drilling Standard: ANSI B16.5 Class 300



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
34	600	25	915	813	24	41	105	BFS-600-25/300

Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

08-02-2024