

Bridas ciegas

Resina Derakane 411 (o equivalente)

Drilling Standard: ANSI B16.5 Class 150



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
1	15	16	98	60	4	16	18	BFS-15-16/150
2	20	16	98	70	4	16	18	BFS-20-16/150
3	25	16	116	79	4	16	20	BFS-25-16/150
4	32	16	116	89	4	16	20	BFS-32-16/150
5	40	16	140	98	4	16	20	BFS-40-16/150
6	50	16	154	121	4	19	20	BFS-50-16/150
7	65	16	184	140	4	19	20	BFS-65-16/150
8	80	10	200	152	4	19	19	BFS-80-10/150
9	80	16	200	152	4	19	25	BFS-80-16/150
10	100	10	228	191	8	19	22	BFS-100-10/150
11	100	16	228	191	8	19	25	BFS-100-16/150
12	125	10	254	216	8	19	22	BFS-125-10/150
13	125	16	254	216	8	19	25	BFS-125-16/150
14	150	10	285	241	8	22	22	BFS-150-10/150
15	150	16	285	241	8	22	28	BFS-150-16/150
16	200	10	350	299	8	22	25	BFS-200-10/150

Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

Bridas ciegas

Resina Derakane 411 (o equivalente)

Drilling Standard: ANSI B16.5 Class 150



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
17	200	16	350	299	8	22	35	BFS-200-16/150
18	250	10	410	362	12	25	35	BFS-250-10/150
19	250	16	410	362	12	25	40	BFS-250-16/150
20	300	10	490	432	12	25	40	BFS-300-10/150
21	300	16	490	432	12	25	48	BFS-300-16/150
22	350	10	540	476	12	29	44	BFS-350-10/150
23	350	16	540	476	12	29	52	BFS-350-16/150
24	400	10	600	540	16	29	48	BFS-400-10/150
25	400	16	600	540	16	29	60	BFS-400-16/150
26	450	10	644	578	16	32	52	BFS-450-10/150
27	450	16	644	578	16	32	68	BFS-450-16/150
28	500	3	720	635	20	32	35	BFS-500-03/150
29	500	6	720	635	20	32	44	BFS-500-06/150
30	500	10	720	635	20	32	60	BFS-500-10/150
31	500	16	720	635	20	32	74	BFS-500-16/150
32	600	3	844	749	20	35	44	BFS-600-03/150
33	600	6	844	749	20	35	52	BFS-600-06/150

Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

Bridas ciegas

Resina Derakane 411 (o equivalente)

Drilling Standard: ANSI B16.5 Class 150



#	DN (mm)	Pmax (bar)	D (mm)	k (mm)	Holes (no.)	d2 (mm)	T (mm)	Article Number
34	600	10	844	749	20	35	68	BFS-600-10/150
35	600	16	844	749	20	35	85	BFS-600-16/150

Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

21-04-2026