



# Coudes

## Coude 30 degrés

Resin Type: Derakane 470



#	DN (mm)	Pmax (bar)	Bend Angle (deg)	ID (mm)	OD (mm)	WT (mm)	RF	R (mm)	Article Number
1	25	16	30	25	33	4	2.0	50	EMC30-25-16/PE
2	40	16	30	40	50	5	2.0	80	EMC30-40-16/PE
3	50	16	30	50	60	5	2.0	100	EMC30-50-16/PE
4	65	16	30	65	77	6	2.0	130	EMC30-65-16/PE
5	80	16	30	80	92	6	2.0	160	EMC30-80-16/PE
6	100	16	30	100	112	6	2.0	150	EMC30-100-16/PE
7	125	16	30	125	139	7	1.5	190	EMC30-125-16/PE
8	150	16	30	150	166	8	1.5	225	EMC30-150-16/PE
9	200	10	30	200	216	8	1.5	300	EMC30-200-10/PE
10	200	16	30	200	222	11	1.5	300	EMC30-200-16/PE
11	250	10	30	250	266	8	1.5	375	EMC30-250-10/PE
12	250	16	30	250	274	12	1.5	375	EMC30-250-16/PE
13	300	10	30	300	318	9	1.5	450	EMC30-300-10/PE
14	300	16	30	300	326	13	1.5	450	EMC30-300-16/PE

### Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.

07-02-2024