

Ellebogen en Bochten

Bocht 45 graden Type PE

Resin Type: Derakane 470



#	DN (mm)	Pmax (bar)	Bend Angle (deg)	ID (mm)	OD (mm)	WT (mm)	RF	R (mm)	Article Number
1	25	16	45	25	33	4	2.0	50	EMC45-25-16/PE
2	40	16	45	40	50	5	2.0	80	EMC45-40-16/PE
3	50	16	45	50	60	5	2.0	100	EMC45-50-16/PE
4	65	16	45	65	77	6	2.0	130	EMC45-65-16/PE
5	80	16	45	80	92	6	2.0	160	EMC45-80-16/PE
6	100	16	45	100	112	6	2.0	150	EMC45-100-16/PE
7	125	16	45	125	139	7	1.5	190	EMC45-125-16/PE
8	150	16	45	150	166	8	1.5	225	EMC45-150-16/PE
9	200	10	45	200	216	8	1.5	300	EMC45-200-10/PE
10	200	16	45	200	222	11	1.5	300	EMC45-200-16/PE
11	250	10	45	250	266	8	1.5	375	EMC45-250-10/PE
12	250	16	45	250	274	12	1.5	375	EMC45-250-16/PE
13	300	10	45	300	318	9	1.5	450	EMC45-300-10/PE
14	300	16	45	300	326	13	1.5	450	EMC45-300-16/PE

Disclaimer

Whilst every care is taken to ensure that the information on this website is complete and accurate, the Rotec Composite Group BV cannot accept responsibility for any omissions or inaccuracies or for any consequences arising therefrom. By using this website, the user accepts the terms of this disclaimer.